
Sound insulating glass 5+12A+5 clear low e insulated glazing glass suppliers China



1, What is 5+12A+5 clear low e insulated glazing glass?

5+12A+5 clear low e insulated glazing glass is using one panel of 5mm clear tempered low e glass and the other of 5mm clear tempered glass panel to form a sound-insulating configuration separated by a 12mm thick aluminum spacer. This configuration will be sealed with the first sealing of butyl sealant and then the second sealing with structural sealant around the insulating glass edges. Sometimes, argon gas will be injected into the insulating chamber to enhance the soundproofing and energy saving functions.



The sound-insulating glass structure

2, Features:

- Super good soundproofing function with noise deduction >30dB+;
- Excellent energy saving function with U value<1.8W/m2K;</p>
- Multiple options for colors appearance by adopting different tinted glass substrate or different coating types(Such as single low e or double low e or solar reflective coating, etc);
- Long lifespan guaranteed(no leaking point);

3, Specifications:

- Production name: 5+12A+5 clear insulated low e glass;
- Glass color: clear, other tinted color such as low iron, gray, bronze, blue, green, etc;
- Glass thickness: 5+5mm, other thickness such as 6+6mm 8+8mm 10+10mm, 12+12mm, or 5+6mm 6+8mm 8+10mm etc all will be available;
- Glass shape: flat/curved;
- Certification: CE/CCC/IS09001/IGCC/AS, etc;
- Packing: Strong plywood crates;

- Samples: Free! Available in 5 days.
- Production time: 15 days after order confirmed;
- Further process: Ceramic frit, frosted, digital printing, etc.

4, Quality:

- Subject to ASTM standard;
- Subject to CE standard;
- Subject to ISO 9001;
- Subject to AS.

5, Excellent energy saving performance:

Typical types of performance data for reference:

发 按 玻璃 Shenzhen Dragon Glass Co., Ltd										
	GI	ass Pe	rforma	ince D	ata					
Configuration	Visible light T%	Visible light Rout%	Visible light Rin%	Solar energy T%	Solar energy Rout%	sc	SHGC	NFRC U- Value Sum.	NFRC U Value Win.	
5mm SDG-I+ 12A + 5mm clear	72	10	12	46	18	0.62	0.54	1.85	1.86	
Smm SDG-II+ 12A + 5mm clear	62	11	12	40	14	0.57	0.50	1,83	1.84	
5mm SDG-IIII+ 12A + 5mm clear	56	20	10	34	21	0.48	0.42	1.81	1.82	
5mm SDG-IV+ 12A + 5mm clear	48	22	10	29	24	0.42	0.37	1.82	1.83	
5mm SDG-V+ 12A + 5mm clear	46	29	12	28	31	0.40	0.35	1.83	1.84	

Energy saving performance data for reference.

Sometimes, argon gas will be adopted to enhance the heat isolating & soundproofing performance. Also, increasing the spacer(12A) or adopting a warm edge spacer will make it higher performance too.

6, Good soundproofing functions:

As one type of the best sound insulating glass products, 5+12A+5 insulated glazing glass has superb sound insulating functions which can ensure you have a good quiet room for rest

and reading. The soundproofing performance as below:

Shenzhen Dragon Glass Co., Ltd Soundproofing Performance Data

Configuration	Calculated	Actual		
	Rw(dB)	Rw(dB)		
6mm	31	26		
10mm	34	29		
5mm low e+9A+5mm clear	33	33		
5mm 1ow e+12A+5mm clear	35	35		

Soundproofing performance data.

7, Applications:


5+12A+5 insulated low e glass can be used in facades, curtain walls, windows, doors, partitions, etc.



Applications

8, Production details:

<u>Shenzhen Dragon Glass</u> as one of the best insulated glazing glass suppliers in China can provide you excellent quality insulated low e glass products at a fast lead time and the best price.



Insulated glass products details.

9, Certifications:



Certifications

10, Packing details:



Packing details.

Are you interested? Welcome to <u>contact us</u> for a free quotation now!